



ELECTRO  **TECH'S**

1875 Sampson Ave., Corona, CA 92879
(951) 734-1812 Fax: (951) 734-5424

12" Lane Control

Specifications

LEDs	High efficiency
Operating temperature	-40° C to +75° C
Dominant wavelength (nm)	See chart below
Power consumption (W)	See chart below
Operating voltage	120 VAC (Other voltages available)
Dimensions	12"
Interconnect	Flange mount
Housing	Water tight, vented polycarbonate

Four Element LED Signal

1. LED matrix
2. Water tight housing
3. Polycarbonate lense
4. Electronic circuitry

Available Now:

Model	Size In (mm)	Voltage (VAC)	Wattage (W)	Color*	λ (nm)	Description	Options	Flange-mount
RD12FM-X	12" (300)	120	6.5	Red	630	Red X	Yellow X, Red Ball, Yellow Ball	✓
YL12FM-X	12" (300)	120	6.5	Yellow	590	Yellow X	Red X, Red Ball, Yellow Ball	✓
12RXGA	12" (300)	120	6.5 – 8	Red / Blue-green	630 / 505	Red X Green Arrow	Yellow X	✓
12BXARROW	12" (300)	120	6.5 – 16	Red Yellow Blue-green	630 / 590 / 505	Red X Yellow Ball Green Arrow	Yellow X, Red Ball	✓

*Other colors are available