



**ELECTRO**  **TECH'S**

1875 Sampson Ave., Corona, CA 92879  
(951) 734-1812 Fax: (951) 734-5424

## 12" X / X / Arrow

### Specifications

---

LEDs	High efficiency
Operating temperature	-40° C to +75° C
Dominant wavelength (nm)	See chart below
Power consumption (W)	See chart below
Operating voltage	120 VAC (Other voltages available)
Dimensions	12"
Interconnect	See chart below
Housing	Water tight, vented polycarbonate

### Four Element LED Signal

---

1. LED matrix
2. Water tight housing
3. Polycarbonate lense
4. Electronic circuitry

### Available Now:

---

Model	Size In (mm)	Voltage (VAC)	Board	Wattage (W)	Color*	$\lambda$ (nm)	Flange- mount
RD12FM-X	12" (300)	120	X	7	Red	630	✓
RY12FM-XX	12" (300)	120	X / X	7 / 7	Red / Yellow	630 / 590	✓
REDX/BGAR-B	12" (300)	120	X / Arrow	7 / 8	Red / Green	630 / 505	✓
RYG12FM-XXA	12" (300)	120	X / X / Arrow	7 / 7 / 8	R / Y / G	630 / 590 / 505	✓

\*Other colors are available