



ELECTRO  **TECH'S**

1875 Sampson Ave., Corona, CA 92879
(951) 734-1812 Fax: (951) 734-5424

8" X / Lane Control

Specifications

LEDs	High efficiency
Operating temperature	-40° C to +75° C
Dominant wavelength (nm)	See chart below
Power consumption (W)	See chart below
Operating voltage	120 VAC (Other voltages available)
Dimensions	8"
Interconnect	Flange mount
Housing	Water tight, vented polycarbonate

Four Element LED Signal

1. LED matrix
2. Water tight housing
3. Polycarbonate lense (Prismatic / tinted available)
4. Electronic circuitry

Available Now:

Model	Size In (mm)	Voltage (VAC)	Wattage (W)	Color*	λ (nm)	Description	Options	Flange- mount
RD08FM-X	8" (200)	120	6	Red	630	Red X	Yellow	✓
YL08FM-X	8" (200)	120	6	Yellow	590	Yellow X	Red	✓
8RXGA	8" (200)	120	6	Red / Blue-green	630 / 505	Red X Green Arrow	Yellow X, R/Y Arrow	✓
8BXARROW	8" (200)	120	6 - 10	Red Yellow Blue-green	630 / 590 / 505	Red X Yellow Ball Green Arrow	Yellow X, Red Ball, R/Y Arrow	✓

*Other colors are available