

1875 Sampson Ave., Corona, CA 92879 (951) 734-1812 Fax: (951) 734-5424

# 12" Ball / Octagon / Triangle / Border

## **Specifications**

**LEDs** 

Operating temperature
Dominant wavelength (nm)

Power consumption (W)

Operating voltage

Dimensions

Interconnect

Housing

High efficiency

-40° C to +75° C

See chart below

See chart below

120 VAC (Other voltages available)

12"

Flange mount

Water tight, vented polycarbonate

### Four Element LED Signal

- 1. LED matrix
- 2. Water tight housing
- 3. Polycarbonate lense (Prismatic available)
- 4. Electronic circuitry

#### **Available Now:**

Model	Size In (mm)	Voltage (VAC)	Wattage (W)	λ (nm)	Description	Options	Flange- mount
IC12RND-GB/ YLOCT	12" (300)	120	12 – 15	505 / 590	Blue-green Ball Yellow Octagon	Color and voltage substitutions	<b>√</b>
IC12RND-GB/ ROCT/ YLTRI	12" (300)	120	12 – 15	505 / 630 / 590	Blue-green Ball Red Octagon Yellow Triangle	Color and voltage substitutions	<b>√</b>

#### Color options for:

Ball\* – Blue-green, pure Green, Blue, White, Purple

Octagon\* - Red, Orange, Yellow

Triangle\* - Red, Orange, Yellow

Border\* – Blue-green, pure Green, Blue, White, Purple

<sup>\*</sup>Typically the border flashes, but flashing is available as desired.