



**ELECTRO**  **TECH'S**

1875 Sampson Ave., Corona, CA 92879  
(951) 734-1812 Fax: (951) 734-5424

## No Left/Right Turn

White arrow in red circle with a red line through the arrow in a 12" retrofit kit.

### Specifications

LEDs	High efficiency
Operating temperature	-40° C to +75° C
Dominant wavelength (nm)	630
Power consumption (W)	See chart below
Operating voltage	120 VAC (Other voltages available)
Dimensions	12"
Interconnect	Flange mount
Housing	Water tight, vented polycarbonate

### Four Element LED Signal

1. LED matrix
2. Water tight housing
3. Polycarbonate
4. Electronic circuitry

### Available Now:

Model	Size In (mm)	Voltage (VAC)	Wattage (W)	Color*	$\lambda$ (nm)	Flange- mount
NXT12	12" (300)	120	13.5	Red / White	630	✓
NXT12-RF*	12" (300)	120	10.2	Red / White	630	✓
NXT12-WF**	12" (300)	120	10.2	Red / White	630	✓
NXT12-AF***	12" (300)	120	7	Red / White	630	✓

Replace the "X" above with an "L" or an "R" indicating the direction not to turn

\* RF – Only the red circle and line flash

\*\* WF – Only the white arrow flashes

\*\*\* AF – Both the white arrow and red circle and line flash